

■ MM1018 QR Stick Steel #1761

Product description

The Quick Repair Stick is a fast-curing 2-component stick, consisting of selected polymers. The sealant is versatile – whether in industrial use, in the home or on the move. In combination with MM1018, the QR-Stick is the savior in need to seal small defects in the shortest possible time. The short time required allows a quick continuation of the assembly.

After curing, the repair site treated with the QR-Stick can be treated like metal.



Characteristics

- Directly and quickly ready for use – without weighing or measuring
- ideal for bonding, filling, sealing of metals
- small & handy
- fast curing within about 15 minutes

Chemical resistance

- Oil
- Petrol
- Coolants

Pack sizes

Article	Description
300 g double cartridge (resin + hardener)	

Custom sizes on request.

Product data condition of delivery

Hue Component A (resin)	darkgrey
Pot life	5-7 min.
Curing 60%	starts from 15 minutes after 1 hour 60% cured
100%	24 hours

Product data (outreacted product)

Compressive strength	86 N/mm ²	DIN 53454
Strength	90	
Tensile strength	25 [N/mm ³ /psi]	DIN 53455
Temperature resistance (permanent)	+120 °C	
color	darkgrey	

Shelf life

Shelf life for 24 months

Processing

1. Knead the heated qrStick in the palm of the hand to a uniform dark grey unit
2. Apply the material manually to the repair site
3. to the desired shape (e. g. press with your finger)

Disposal

Unused material can be disposed of normally when mixed in the correct ratio and fully cured (EAKV 170203). Unmixed material must be disposed of as chemical waste (EAKV 080111). When booking our **DIAMANT application service**, we take care of the professional and correct disposal of the waste.

Qualification and service

To ensure the best possible quality and error-free application, we offer the following services:

- Product training
- Site supervision and monitoring (Supervising)

- Complete execution of the work by our experienced application technicians or installers

Contact us, we will be happy to advise you and are immediately available.

Safety data sheet

Please read the corresponding safety data sheet before processing the product. Material Safety Data Sheets are available on a daily basis upon request via info@diamant-polymer.de or by phone +49-2166-98360. DIAMANT guarantees the product properties as long as they are stored and used according to the specifications listed here. DIAMANT does not assume any responsibility for the processing of the material. Our technicians will be happy to answer any further questions you may have.

value entry

Disclaimer

The following supersedes the buyer's documents. Seller makes no express or implied representations or warranties, including merchantability or fitness for a particular purpose. Although the advice and information contained in this publication is based on our own findings and is believed to be reliable, we cannot accept any responsibility for the suitability or results of the processing of the products described herein, nor for any loss or damage caused directly or indirectly by the processing of our products. The processor is obliged to test the quality, safety and other relevant properties before using the described products. We guarantee the flawless quality of our products in accordance with our General Terms and Conditions. The Buyer's sole remedy and the Seller's sole liability for any claims are the Buyer's purchase price. No reference in this document may be construed as an incentive, recommendation or permission to disregard existing intellectual property rights. When handling our products, the industrial hygiene and legal regulations must be observed. For further information, please refer to the relevant safety data sheets. This edition replaces all previous versions